

# The most user friendly Security Alarm System

with the patent-pending two-wire technology

New  
Simple  
Professional  
DIY

LS400  
Control Panel



Two non-polarity flat wires

Two non-polarity flat wires

Two non-polarity flat wires



External Siren  
GOMBELL



Magnetic Contacts  
MRS101



Two-wire  
PIR TW402

## Four zone two-wire Alarm System **LS400**

LY52-000-33

### Easy Installation

- only simple two-conductor flat wires are used and with no polarity restriction

### Simple Operation

- Convenient Home, Out and Off three mode operation with push buttons

### User Friendly

- Home and Out modes are pre-programmed, no tedious and complicated user programming is required

### Expandable system

- With built-in easy connection to Voice dialler for added security
- Can connect two PIR's to one zone; therefore total four PIR's to one system

### Full function

- Four-digit PIN code for disarm, plus Duress code and Panic Alarm code for emergencies
- Selectable exit/ entrance delay time available
- Door chime function available for Off mode operation
- Alarm-hold indication and Low Battery indication are provided
- Built-in Siren sounder plus additional external Siren capability

\*All connections are simply by 2 non-polarity flat wires only.

[www.lynteck.co.uk](http://www.lynteck.co.uk)




Lynteck, Churchill Way, Nelson, Lancashire BB9 6RT email: [sales@lynteck.co.uk](mailto:sales@lynteck.co.uk)  
[www.lynteck.co.uk](http://www.lynteck.co.uk) Tel: 01282 717 490 Fax: 01282 698 020  
Technical Support (Mon-Fri 9am-5pm): 0906 711 2329 (calls charged at 50p per min)  
Company policy is one of continuous improvement,  
we reserve the right to change specification without prior notice.



# Four Zone Two Wire Alarm System

## LS 400 Two Wire Magnetic Contact (LY52-010-35)



- Magnetic Switch detects the opening of doors & windows
- Reliable & Versatile
- Quick & easy to install

### Specification

Type:	Magnetically activated switch
Housing:	ABS

## LS 400 Two Wire External Bell Box (LY52-011-36)



- High output Piezo Sounder
- Use inside & outside
- Quick & easy to install

### Specification

Type:	External Siren
Housing:	ABS
Siren Output:	110dB at 1m
Lens Colour:	Blue

## LS 400 Two Wire PIR (LY52-012-37)



- Sealed Detection Sensor
- Elimination of creep zones
- Hemispherical Lens
- Coverage up to 15m
- Selectable Pulse count

### Specification

Type:	Dual element with hemispherical lens
Housing:	ABS
Test LED:	Selectable (on/off)
Mounting Height:	2m
Detection Range:	Upto 15m

## LS 400 Two Wire Voice Dialler (LY52-013-38)



- Microprocessor Based Voice Dialler
- Dial up to 3 numbers
- 20 second single voice message
- Non-Volatile memory

### Specification

Type:	Microprocessor based
Housing:	ABS